



INSTITUTE OF AERONAUTICAL ENGINEERING
(Autonomous)
Dundigal, Hyderabad - 500 043

Lab Manual:

SURVEYING AND GEOMATICS LABORATORY(ACEC05)

Prepared by

MR. A JAGADISH BABU (IARE10679)

DEPARTMENT OF CIVIL ENGINEERING
INSTITUTE OF AERONAUTICAL ENGINEERING

December 20, 2021

Contents

| Content | iii |
|---|----------|
| 1 INTRODUCTION | 1 |
| 1.1 INTRODUCTION | 1 |
| 1.1.1 Student Responsibilities | 1 |
| 1.1.2 Responsibilities of Faculty Teaching the Lab Course | 1 |
| 1.1.3 Laboratory In-charge Responsibilities | 1 |
| 1.1.4 Course Coordinator Responsibilities | 1 |
| 1.2 LAB POLICY AND GRADING | 2 |
| 1.3 COURSE GOALS AND OBJECTIVES | 2 |
| 1.4 USE OF LABORATORY INSTRUMENTS | 2 |
| 1.4.1 Instrument Protection Rules | 3 |
| 1.5 DATA RECORDING AND REPORTS | 3 |
| 1.5.1 The Laboratory Notebook: | 3 |
| 1.5.2 The Laboratory Worksheets: | 4 |
| 2 LAB-1 INTRODUCTION TO SURVEYING LABORATORY-I | 5 |
| 2.1 DEFINITION: | 5 |
| 3 LAB-2 SURVEY OF AN AREA BYCHAIN SURVEY (CLOSED TRAVERSE) AND PLOTTING | 6 |
| 3.1 OBJECTIVE: | 6 |
| 3.2 RESOURCES: | 6 |
| 3.3 PRECAUTIONS: | 6 |
| 3.4 FIGURE: | 6 |
| 3.5 PROCEDURE: | 6 |
| 3.5.1 Ranging a line: | 6 |
| 3.5.2 Taking offsets: | 6 |
| 3.5.3 Procedure for surveying the given open field (Closed Traverse): | 7 |
| 3.6 AREA CALCULATIONS: | 7 |
| 3.7 RESULTS: | 7 |
| 3.8 PROBING FURTHER QUESTIONS: | 7 |
| 4 LAB-3 CHAINING ACROSS OBSTACLES | 8 |
| 4.1 OBJECTIVE: | 8 |
| 4.2 RESOURCES: | 8 |
| 4.3 PRECAUTIONS: | 8 |
| 4.4 PROCEDURE: | 8 |
| 4.5 NOMENCLATURE: | 9 |
| 4.6 RESULTS | 9 |
| 4.7 FURTHER PROBING EXPERIMENTS | 10 |

| | | |
|----------|--|-----------|
| 5 | LAB-4 DETERMINE OF DISTANCE BETWEEN TWO INACCESSIBLE POINTS WITH COMPASS | 11 |
| 5.1 | OBJECTIVE: | 11 |
| 5.2 | RESOURCES: | 11 |
| 5.3 | PRECAUTIONS: | 11 |
| 5.4 | THEORY: | 11 |
| 5.5 | DESCRIPTION: | 12 |
| 5.6 | PROCEDURE: | 12 |
| 5.7 | NOMENCLATURE: | 13 |
| 5.8 | RESULTS | 13 |
| 5.9 | FURTHER PROBING EXPERIMENTS | 13 |
| 6 | LAB-5 SURVEYING OF A GIVEN AREA BY PRISMATIC COMPASS(CLOSED TRAVERSE) AND P;OTTING AFTER ADJUSTMENT | 14 |
| 6.1 | OBJECTIVE: | 14 |
| 6.2 | RESOURCES: | 14 |
| 6.3 | SPECIFICATIONS: | 14 |
| 6.4 | PROCEDURE: | 15 |
| 6.5 | GRAPHS: | 15 |
| 6.6 | TYPICAL CALCULATION: | 16 |
| 6.7 | OBSERVATIONS: | 16 |
| 6.8 | RESULTS: | 17 |
| 6.9 | FURTHER PROBING EXPERIMENTS | 17 |
| 7 | LAB-6 CORRECTION FOR LOCAL ATTRACTION BY PRISMATIC COMPASS. | 18 |
| 7.1 | OBJECTIVE | 18 |
| 7.2 | RESOURCES: | 18 |
| 7.3 | PRECAUTIONS: | 18 |
| 7.4 | PROCEDURE: | 18 |
| 7.5 | RESULTS: | 18 |
| 7.6 | FURTHER PROBING EXPERIMENTS | 19 |
| 8 | LAB-7 RADIATION METHOD, INTERSECTION METHODS BY PLANE TABLE SURVEY | 20 |
| 8.1 | OBJECTIVE: | 20 |
| 8.2 | RESOURCES: | 20 |
| 8.3 | PRECAUTIONS: | 20 |
| 8.4 | THEORY: | 20 |
| 8.5 | PROCEDURE: | 20 |
| 8.6 | TYPICAL TEST OBSERVATION: | 21 |
| 8.7 | RESULTS: | 21 |
| 8.8 | FURTHER PROBING EXPERIMENTS | 22 |
| 9 | LAB-8 TWO POINT PROBLEM IN PLANE TABLE SURVEY | 23 |
| 9.1 | OBJECTIVE: | 23 |
| 9.2 | RESOURCES: | 23 |
| 9.3 | Theory: | 23 |
| 9.4 | PROCEDURE: | 24 |
| 9.5 | RESULTS: | 25 |
| 9.6 | FURTHER PROBING EXPERIMENTS | 25 |

| | |
|---|-----------|
| 10 LAB-9 THREE POINT PROBLEM IN PLANE TABLE SURVEY | 26 |
| 10.1 OBJECTIVE: | 26 |
| 10.2 RESOURCES: | 26 |
| 10.3 THEORY: | 26 |
| 10.4 PROCEDURE: | 29 |
| 10.5 RESULT | 29 |
| | |
| 11 LAB-10 TRAVERSING BY PLANE TABLE SURVEY | 30 |
| 11.1 OBJECTIVE: | 30 |
| 11.2 RESOURCES: | 30 |
| 11.3 PRECAUTIONS: | 30 |
| 11.4 PROCEDURE: | 30 |
| 11.5 GRAPH: | 31 |
| 11.6 RESULTS: | 31 |
| 11.7 FURTHER PROBING EXPERIMENTS | 31 |

INTRODUCTION

1.1 INTRODUCTION

1.1.1 Student Responsibilities

The student is expected to come prepared for each lab. Lab preparation includes understanding the lab experiment from the lab manual and reading the related textbook material.

Students have to write the allotted experiment for that particular week in the work sheets given and carry them to the Lab. In case of any questions or problems with the preparation, students can contact the Faculty Teaching the Lab course, but in a timely manner.

Students have to be in formal dress code, wear shoes and lab coat for the Laboratory Class.

After the demonstration of experiment by the faculty, student has to perform the experiment individually. They have to note down the observations in the observation Tables drawn in work sheets, do the calculations and analyze the results.

Active participation by each student in lab activities is expected. The student is expected to ask the Faculty any questions they may have related to the experiment.

The student should remain alert and use commonsense while performing the lab experiment. They are also responsible for keeping a professional and accurate record of the lab experiments in the files provided.

1.1.2 Responsibilities of Faculty Teaching the Lab Course

The Faculty shall be completely familiar with each lab prior to the laboratory. He/She shall provide the students with details regarding the syllabus and safety review during the first week. Lab experiments should be checked in advance to make sure that everything is in working order. The Faculty should demonstrate and explain the experiment and answer any questions posed by the students. Faculty have to supervise the students while they perform the lab experiments. The Faculty is expected to evaluate the lab worksheets and grade them based on their practical skills and understanding of the experiment by taking Viva Voce. Evaluation of work sheets has to be done in a fair and timely manner to enable the students, for uploading them online through their CMS login within the stipulated time.

1.1.3 Laboratory In-charge Responsibilities

The Laboratory In-charge should ensure that the laboratory is properly equipped, i.e., the Faculty teaching the lab receive any equipment/components necessary to perform the experiments. He/She is responsible for ensuring that all the necessary equipment for the lab is available and in working condition. The Laboratory In-charge is responsible for resolving any problems that are identified by the teaching Faculty or the students.

1.1.4 Course Coordinator Responsibilities

The course coordinator is responsible for making any necessary corrections in Course Description and lab manual. He/She has to ensure that it is continually updated and available to the students

in the CMS learning Portal.

1.2 LAB POLICY AND GRADING

The student should understand the following policy:

ATTENDANCE: Attendance is mandatory as per the academic regulations.

LAB RECORD's: The student must:

1. Write the work sheets for the allotted experiment and keep them ready before the beginning of eachlab.
2. Keep all work in preparation of and obtained during lab.
3. Perform the experiment and record the observations in the worksheets.
4. Analyze the resultsand get the work sheets evaluated by the Faculty.
5. Upload the evaluated reports online from CMS LOGIN within the stipulated time.

Grading Policy:

The final grade of this course is awarded using the criterion detailed in the academic regulations. A large portion of the student's grade is determined in the comprehensive final exam of the Laboratory course (SEE PRACTICALS),resulting in a requirement of understanding the concepts and procedure of each lab experiment for successful completion of the lab course.

Pre-Requisites and Co-Requisties:

The lab course is to be taken during the samesemester as AHSC03, but receives a separate grade. Students are required to have completed both AHSC03 and AHSC05 with minimum passing grade or better grade in each.

1.3 COURSE GOALS AND OBJECTIVES

I The types of surveys, methods and technology involved in measuring field parameters using traditional and modern instruments.

II The operating principles of various levelling instruments and analyze their performance characteristics under various terrains.

III The measurement of alteration works, detecting land use and land cover, creating base maps for visual reference.

1.4 USE OF LABORATORY INSTRUMENTS

One of the major goals of this lab is to familiarize the student with the proper equipment andtechniques for conducting experiments. Some understanding of the lab instruments is necessaryto avoid personal or equipment damage.By understanding the device's purpose and following a fewsimple rules, costly mistakes can be avoided.

The following rules provide a guideline for instrument protection.

1.4.1 Instrument Protection Rules

1. New students must receive an orientation on lab operating procedures before working in a lab.
2. Students shall publish a safety checklist for equipment for which they are responsible.
3. Students must read the safety checklist for each piece of equipment before operating it.
4. Ensure you know the location of the emergency stop button before starting equipment.
5. Always depressurize accumulators or pneumatic reservoirs before working on fluid power apparatus.
6. Check the application pressure, system pressure, and component pressure before connecting a system to a pump or pressure source. The maximum operating pressures are listed on equipment labels or published on manufacturer websites.
7. Periodically check hoses for leakage, cracks, kinks, or breaks.
8. Test your equipment for leaks at low pressure before raising the pressure to the operating pressure.
9. All components shall operate within manufacturer's specifications.
10. Equipment shall incorporate an emergency stop or emergency return control, whichever provides maximum safety.
11. Emergency stops shall be readily accessible under all conditions of working and shall operate immediately.
12. Equipment shall be designed so that loss of electrical, pneumatic and/or hydraulic power shall not cause a hazard.
13. Pump inlet temperatures should not exceed 600C when maximum ambient temperatures exist.
14. Rotating parts shall be guarded to provide adequate protection against hazard.
15. Flexible hoses shall only be used where necessary. Their length shall be minimized and they shall be protected from abrasion. If failure causes a hazard, the hose shall be restrained or shielded.

1.5 DATA RECORDING AND REPORTS

1.5.1 The Laboratory Notebook:

Students must record their experimental values in the provided tables in this laboratory manual and reproduce them in the lab reports. Reports are integral to recording the methodology and results of an experiment. In engineering practice, the laboratory notebook serves as an invaluable reference to the technique used in the lab and is essential when trying to duplicate a result or write a report. Therefore, it is important to learn to keep accurate data. Make plots of data and sketches when these are appropriate in the recording and analysis of observations. Note that the data collected will be an accurate and permanent record of the data obtained during the experiment and the analysis of the results. You will need this record when you are ready to prepare a lab report.

1.5.2 The Laboratory Worksheets:

Reports are the primary means of communicating your experience and conclusions to other professionals. In this course you will use the lab report to inform your LTA about what you did and what you have learned from the experience. Engineering results are meaningless unless they can be communicated to others. You will be directed by your LTA to prepare a lab report on a few selected lab experiments during the semester. Your assignment might be different from your lab partner's assignment.

Your laboratory report should be clear and concise. The lab report shall be typed on a word processor. As a guide, use the format on the next page. Use tables, diagrams, sketches, and plots, as necessary to show what you did, what was observed, and what conclusions you can draw from this. Even though you will work with one or more lab partners, your report will be the result of your individual effort in order to provide you with practice in technical communication.

CONCLUSIONS - The conclusion section should provide a take-home message summing up what has been learned from the experiment:

1. Briefly restate the purpose of the experiment (the question it was seeking to answer)
2. Identify the main findings (answer to the research question)
3. Note the main limitations that are relevant to the interpretation of the results
4. Summarise what the experiment has contributed to your understanding of the problem.

LAB-1 INTRODUCTION TO SURVEYING LABORATORY-I

2.1 DEFINITION:

Surveying is the science and art of making all essential measurements to determine the relative position of points or physical and cultural details above, on, or beneath the surface of the Earth, and to depict them in a usable form, or to establish the position of points or details.

1. Introduction to principle of surveying
2. Introduction to chain surveying and their components, types of chains, errors in chain surveying, corrections for chain surveying, principles and procedures.
3. Introduction to tape surveying and their components, types of tapes, errors in tape surveying, corrections for tape surveying, principles and procedures.
4. Introduction to compass surveying and their components, types of compass, errors in compass, corrections for local attraction, principles and procedures.
5. Introduction to plane table surveying and their components, types of plane tables.
6. Introduction to leveling instruments and their components, types of leveling instruments, correction for curvature and refraction.
7. Introduction to contours, types of contours and methods of plotting contours.
8. Introduction to plot longitudinal section and cross section.

LAB-2 SURVEY OF AN AREA BYCHAIN SURVEY (CLOSED TRAVERSE) AND PLOTTING

3.1 OBJECTIVE:

To survey an open field by chain survey in order to calculate an area of the field.

3.2 RESOURCES:

To study the gyroscopic effect of a rotating disc.

3.3 PRECAUTIONS:

1. Chainages must be marked against the working edge of the offset scale.
2. The plan must be so oriented on the sheet that the north side of the survey lies towards the top of the sheet.
3. Each triangle must be verified by measuring the check lines.

3.4 FIGURE:

3.5 PROCEDURE:

3.5.1 Ranging a line:

It is the process of establishing a number of intermediate points on a survey line joining two stations in the field, so that all the points on the line are in alignment and the length between stations may be measured accurately. Two ranging rods are erected vertically at the end stations by two surveyors who are standing behind ranging rods. One of the surveyors from one of the end stations directs the assistant to hold the ranging rod vertically to establish an intermediate point and move the rod either to the left or right until the ranging rod is in alignment with the end stations. Finally, when the ranging is correct, the assistant is directed to fix the ranging rod at that point. All the directions from surveyor should be as per the Code of Signals given in Table 1.

3.5.2 Taking offsets:

The perpendicular distance measured right or left of the chain line to locate the details like corners, boundaries, culverts, etc is known as offset. Offsets can be taken by two ways: 1. By Tape and 2. By Cross-Staff.

By Tape:

The leader holds the zero end of the tape at the point where the offset is to be taken and the follower swings off the tape in an arc across the chain line to left and right. The minimum

reading of tape on the chain line gives the position of the foot of the perpendicular from the required point.

By Cross-Staff:

The Cross-Staff is held vertically on the chain line approximately near the point where the offset is likely to fall. The Cross-Staff is turned until the signal at one end of the chain line is viewed through one pair of slits. The surveyor then takes a round and views through the other pair of slits. If the point to which the offset is to be taken is seen, the point below the instrument is the required foot of the offset. On the other hand, if the point is not seen, the surveyor moves along the chain line, without twisting the CrossStaff, till the point appears.

3.5.3 Procedure for surveying the given open field (Closed Traverse):

ABCDEF is the required closed traverse open field to be surveyed for calculating the area as shown in Fig 1. From the station A the length of all the opposite corners such as AC, AD and AE are measured with a chain and the longest distance is considered for laying off the main chain line. In this case AD is the longest and a chain line running from A to D is laid. Offsets to corner points B, C, E and F are now laid from the chain line AD either by tape or cross-staff and their foot of offsets are G, I, J, H respectively. All the offset lengths GB, HF, IC and JE are measured either by chain or tape depending on the length of offsets. The distances between all the points AG, GH, HI, IJ and JD are also measured along the chain line

3.6 AREA CALCULATIONS:

3.7 RESULTS:

The total Area of the given Open Field by Chain Survey =sqm

3.8 PROBING FURTHER QUESTIONS:

1. How the offsets are taken in the field?
2. What are the precautions are to be taken in erecting perpendiculars?
3. What is indirect ranging and how it can be done?
4. What is base line and check line?

LAB-3 CHAINING ACROSS OBSTACLES

4.1 OBJECTIVE:

CONDITIONS FOR STATIC BALANCING:

If a shaft carries a number of unbalanced masses such that the center of mass of the system lies on the axis of rotation, the system is said to statically balance.

BALANCING OF SEVERAL MASSES ROTATING IN DIFFERENT PLANES:

When several masses revolve in different planes, they may be transferred to a reference plane (written as RP), which may be defined as the plane passing through a point on the axis of rotation and perpendicular to it. The effect of transferring a revolving mass (in one plane) to a reference plane is to cause a force of magnitude equal to centrifugal force of the revolving mass to act in the reference plane, together with a couple of magnitude equal to the product of the force and the distance between the plane of rotation and the reference plane. In order to have a complete balance of the several revolving masses in different planes, the following conditions must be satisfied:

1. The forces in the reference plane must balance, i.e. the resultant force must be zero.
 2. The couple about the reference plane must balance, i.e. the resultant couple must be zero.
- Let us now consider four masses m_1 , m_2 , m_3 and m_4 revolving in planes 1, 2, 3 and 4 shown in fig. The relative angular positions of these masses are shown in the end view

Fig. The magnitude, angular position and position of the balancing mass m_1 in plane 1 may be obtained as discussed below:

1. Take one of the planes, say 1 as the reference plane (R.P.). The distance of all the other planes to the left of the reference plane may be regarded as negative, and those to the right as positive.
2. Tabulate the data as in table. The planes are tabulated in the same order i.e. 1, 2, RP

4.2 RESOURCES:

To balance the masses statically of a simple rotating mass system and to observe the effect of unbalance in a rotating mass system.

4.3 PRECAUTIONS:

Study about rotating balancing system

4.4 PROCEDURE:

1. Insert all the weights in sequence 1- 2- 3 - 4 from pulleyside.

2. Fix the pointer and pulley on shaft.
3. Fix the pointer on θ (θ_2) on the circular protractor scale.
4. Fix the weight no. 1 in horizontal position.
5. Rotate the shaft after loosening previous position of pointer and fix it on θ_3 .
6. Fix the weight no. 2 in horizontal position.
7. Loose the pointer and rotate the shaft to fix pointer on θ_4 .
8. Fix the weight no. 3 in horizontal position.
9. Loose the pointer and rotate the shaft to fix pointer on θ_1 .
10. Fix the weight no.4 in horizontal position.
11. Now the weights are mounted in correct position.
12. For static balancing, the system will remain steady in any angular position.
13. Now put the belt on the pulleys of shaft and motor.
14. Supply the main power to the motor through dimmerstat.
15. Gradually increase the speed of the motor. If the system runs smoothly and without vibrations, it shows that the system is dynamically balanced.
16. Gradually reduce the speed to minimum and then switch off the main supply to stop the system.

4.5 NOMENCLATURE:

L = Distance between particular weight from weight 1, mm
 W = Mass of particular weight, kg
 θ = Angle of particular weight from Reference Point, degree

4.6 RESULTS

Obstacles to measurement:

Obstructed length from First Method = m

Obstructed length from Second Method = m

Obstructed length from Third Method = m

Obstacles to alignment:

Obstructed length from First Method = m

4.7 FURTHER PROBING EXPERIMENTS

1. Write the importance of balancing?
2. Differentiate: static and dynamic balancing.
3. Can a single cylinder engine be fully balanced? Why?
4. Define tractive force.
5. What are the effects of hammer blow and swaying couple?

LAB-4 DETERMINE OF DISTANCE BETWEEN TWO INACCESSIBLE POINTS WITH COMPASS

5.1 OBJECTIVE:

CONDITIONS FOR DYNAMICBALANCING:

If a shaft carries a number of unbalanced masses such that the center of mass of the system lies on the axis of rotation, the system is said to statically balance. The resultant couple due to all the inertia forces during rotation must be zero.

These two conditions together will give complete dynamic balancing. It is obvious that a dynamically – balanced system is also statically balanced, but the statically balanced system is not dynamically balanced.

5.2 RESOURCES:

To balance the masses Statically & Dynamically of a simple rotating mass system and to observe the effect of unbalance in a rotating mass system.

5.3 PRECAUTIONS:

This experiment is to be fusion of two pieces of metal by an electric arc between the pieces being joined. So, the working of Arc welding machine and the components available for the machine and procedure of the manufacture. So how the welding is been done can be studied on course AMEB05 so before doing the experiment be prepared with the prelab preparation of welding /joining.

5.4 THEORY:

BALANCING OF SEVERAL MASSES ROTATING IN DIFFERENT PLANES:

When several masses revolve in different planes, they may be transferred to a reference plane (written as RP), which may be defined as the plane passing through a point on the axis of rotation and perpendicular to it. The effect of transferring a revolving mass (in one plane) to a reference plane is to cause a force of magnitude equal to centrifugal force of the revolving mass to act in the reference plane, together with a couple of magnitude equal to the product of the force and the distance between the plane of rotation and the reference plane. In order to have a complete balance of the several revolving masses in different planes, the following conditions must be satisfied:

1. The forces in the reference plane must balance, i.e. the resultant force must be zero.

2. The couple about the reference plane must balance, i.e. the resultant couple must be zero.

Let us now consider four masses m_1 , m_2 , m_3 and m_4 revolving in planes 1, 2, 3 and 4 shown in fig. The relative angular positions of these masses are shown in the end view

Fig. The magnitude, angular position and position of the balancing mass m_1 in plane 1 may be obtained as discussed below:

1. Take one of the planes, say 1 as the reference plane (R.P.). The distance of all the other planes to the left of the reference plane may be regarded as negative, and those to the right as positive.
2. Tabulate the data as in table. The planes are tabulated in the same order i.e. 1, 2, 3, RP

5.5 DESCRIPTION:

The apparatus consists of a steel shaft mounted in ball bearings in a stiff rectangular main frame. A set of four blocks of different weights is provided and may be detached from the shaft. A disc carrying a circular protractor scale is fitted to one side of the rectangular frame. A scale is provided with the apparatus to adjust the longitudinal distance of the blocks on the shaft. The circular protractor scale is provided to determine the exact angular position of each adjustable block. The shaft is driven by electric motor mounted under the main frame, through a belt. For static balancing of weights the main frame is suspended to support frame by chains then rotate the shaft manually after fixing the blocks at their proper angles. It should be completely balanced. In this position, the motor for dynamic balancing of the rotating mass system, the main frame is suspended from the support frame by two short links such that the main frame and the supporting frame are in the same plane. Rotate the statically balanced weights with the help of motor. If they rotate smoothly and without vibrations, they are dynamically balanced or driving belt should be removed.

5.6 PROCEDURE:

1. Insert all the weights in sequence 1- 2- 3 - 4 from pulleyside.
2. Fix the pointer and pulley on shaft.
3. Fix the pointer on θ_0 (θ_2) on the circular protractor scale.
4. Fix the weight no. 1 in horizontal position.
5. Rotate the shaft after loosening previous position of pointer and fix it on θ_3 .
6. Fix the weight no. 2 in horizontal position.
7. Loose the pointer and rotate the shaft to fix pointer on θ_4 .
8. Fix the weight no. 3 in horizontal position.
9. Loose the pointer and rotate the shaft to fix pointer on θ_1 .
10. Fix the weight no.4 in horizontal position.
11. Now the weights are mounted in correct position.
12. For static balancing, the system will remain steady in any angular position.

13. Now put the belt on the pulleys of shaft and motor.
14. Supply the main power to the motor through dimmerstat.
15. Gradually increase the speed of the motor. If the system runs smoothly and without vibrations, it shows that the system is dynamically balanced.
16. Gradually reduce the speed to minimum and then switch off the main supply to stop the system.

5.7 NOMENCLATURE:

L = Distance between particular weight from weight 1, mm
 W = Mass of particular weight, kg
 θ = Angle of particular weight from Reference Point, degree

5.8 RESULTS

The distance between the two inaccessible points A and B = m

5.9 FURTHER PROBING EXPERIMENTS

1. Write the importance of balancing?
2. Differentiate: static and dynamic balancing.
3. Can a single cylinder engine be fully balanced? Why?
4. Define tractive force.
5. What are the effects of hammer blow and swaying couple?

LAB-5 SURVEYING OF A GIVEN AREA BY PRISMATIC COMPASS(CLOSED TRAVERSE) AND P;OTTING AFTER ADJUSTMENT

6.1 OBJECTIVE:

To Determine the Balancing Forces and Reciprocating Masses
section Equipment needed

- Reciprocating Masses Test rig

6.2 RESOURCES:

The Mathematical analysis of the behavior of journal in a bearing falls into two distinct categories as given in the appendix of this manual. They are,

- 1) Hydrodynamics of fluid flow between plates.
- 2) Journal bearing analysis where the motion of the journal in the oil film is considered.

According to equation the Sommerfield pressure function (When the velocity of the eccentricity and the whirl speed of the journal are both zero) is given by

Where P is the pressure of the oil film at the point measured clockwise from the line of common centers (00) and $P = P_0$ at $\theta = 0$ and $\theta = \pi$ refer the fig.

Note: – Some books on lubrication give the Sommerfield function with a negative sign for n . This is true if it is measured from the point of minimum thickness of the oil film that is

$$h = \delta(1 - n \cos \theta)$$

It is also proved in the analysis that maximum pressure occurs at

$$\cos \theta_m = \frac{3m}{2 + n^2}$$

6.3 SPECIFICATIONS:

1. Diameter of Journal = (A) = $2R = 55\text{mm}$
2. Diameter of bearing = (E) = $2r = 70\text{mm}$ (With 16 radial tapings)
3. Bearing width = (L) = 15mm
4. Weight of bearing with attachment = 1.7 kg
5. Weight of balancing load = (J) =
6. Set of weights is provided.

7. Motor D. C. = 0.5 HP, 1500 rpm. Variable speed.
8. Dimmer state is provided for speed variation.
9. Manometer board with 16 tubes and suitable height with suitable scales and adjustable oil tank.
10. Recommended oil = Lubricating oil SAE 20 or SAE 30.
11. Supply required = A. C., 1 HP, 230 V., 50 c/sec., stabilized.

6.4 PROCEDURE:

1. Fill the oil tank by using SAE 20 or SAE 30 lubricating oil under test and position the tank at the desired height.
2. Drain out the air from all the tubes on the manometer and check level balance with supply level indicator.
3. Check that some oil leakage is there. Some leakage of oil is necessary for cooling purpose.
4. Check the direction of rotation and increase the speed of the motor slowly.
5. Set the speed and let the journal run for about half an hour until the oil in the bearing is warmed up and check the steady oil levels at various tapings.
6. Add the required loads and keep the balancing rod in horizontal position by moving balancing weight "J" on the rod and observe the steady levels.
7. When the manometer levels have settled down, take the pressure readings on 1 to 12 manometer tubes. For circumferential pressure distribution and A-B-12-C-D tubes for axial pressure distribution.
8. Repeat the experiment for various speeds and loads.
9. After the test is over set dimmer to zero position and switch off main supply.
10. Keep the oil tank at lower most position so that there will be no leakage in the idle period.

6.5 GRAPHS:

1. Graph to be plotted for pressure head of oil above supply head in cm. of oil, at angular intervals of 30° of oil film. The angular interval position are measured clockwise, commencing with position marked "1" in Fig.
2. Graph is drawn for theoretical and experimental pressure curves for journal $N_1 = NRPM$.
3. Graph is plotted for experimental pressure curves along the length of bearing at these speeds.

6.6 TYPICAL CALCULATION:

These calculations are based on sample readings and will differ from actual results and calculations for different unit. Data used in calculation is not pertaining to the actual unit supplied. The method of drawing the theoretical Sommerfeld pressure curve is as follows: Consider pressure curve for $N_1 = N$ RPM.

- Select two points A and B on the experimental pressure curve of equal pressure and 180° apart.
- Note that for any pressure curve there will be only one such pair of points is possible. These two points A and B from the axis $P - P_0 = 0$ for the Sommerfeld curve.
- Of these two points take the point which is maximum thickness of oil film and take $\theta = 0$ to pass through this point.
- From the graph determine the point of maximum pressure ($P - P_0$) max. in this case $\theta = 206^\circ = -3n/2 + n^2$ $n = 0.8$
 Also $176 = \frac{-K \sin 206^\circ (2 + 0.8 \cos 206^\circ)}{1 + 0.8 \cos 206^\circ}$ $k=24.5$
- Now plot the curve $P - P_0 =$ (with B as origin)

Load on the bearing

Total vertical load on bearing at NRPM.

= Dry weight of Bearing + Weight added + Weight of balancing load.

= $1.375 + 2 \times 0.150 +$ added weight nil.

= 1.675 Kg.

Referring to fig. the mean positive pressure head of the oil above supply head.

= $(35.5 + 24 + 18 + 12 + 8 + 5 + 2 + 60 + 177 + 130) / 10$.

= 45.5 cm.

Load carried by oil pressure on projected area of bearing

= $45.5 \times$ Density of oil $\times (2 R) L$.

= $45.5 \times 0.8539 \times 5.5 \times 6.8$.

= 1.450 kg.

The underlined figures are recorded from graph and balanced are practical result.

Maximum theoretical load on journal is **Table 1:**

Typical Results w. r. t. manometer tubes.

Table 2: PRESSURE HEAD OF OIL FILM ABOVE HEAD = $(P - P_s)$ cm.

Shaft speed = RPM.

6.7 OBSERVATIONS:

The Sommerfeld pressure function agrees with the experimental pressure curve within reasonable limits as indicated in Fig. Any deviations between the experimental and theoretical curves can be due to –

1. Human error in taking readings, for example in deciding whether or not the oil levels in the manometer are absolutely steady before taking reading.

2. The theoretical analysis is based on the assumption that the thickness of the oil film $h = \delta + e \cos \theta$ which is true only if the radial clearance is very small. In practical journal bearings this assumption is true but in this test rig $\theta = 2.5$ mm. which is very large. This has been purposely done so that the oil film profile is clearly visible.
3. The total weight of the bearing is = 1.375 Kg. It can be seen that the oil film in the bearing does not carry this full weight, a part of weight appears to be taken by the seal, and the flexible plastic tubes attached to the bearing.

6.8 RESULTS:

Distances:

AB = m

BC = m

CD = m

DE = m

EA = m

Included Angles:

Angle A =

Angle B =

Angle C =

Angle D =

Angle E =

6.9 FURTHER PROBING EXPERIMENTS

1. The journal bearings are generally used in.
2. The basic type of motion of a body is not the translation motion only.
3. Coplanar forces are not easily simplified in the simplification of the force and couple system in the calculations of forces in the journal bearings.
4. The moment of the force is the product of the force and the perpendicular distance of the axis and the point of action of the force. Is this also true for rolling?
5. If a car is moving forward, what is the direction of the moment of the moment caused by the rolling of the tires, assume non slippery surface?

LAB-6 CORRECTION FOR LOCAL ATTRACTION BY PRISMATIC COMPASS.

7.1 OBJECTIVE

To study the longitudinal vibration of helical spring and to determine the frequency and time period of oscillation theoretically and actually by experiment.

7.2 RESOURCES:

Get complete detail of Springs and there stiffness and also how test rig works

7.3 PRECAUTIONS:

1. The plan must be so oriented on the sheet that the north side of the survey lies towards the top of the sheet
2. Temporary adjustments must be done carefully.
3. Compass readings must be taken with full accuracy
4. Care must be taken while centering the compass

7.4 PROCEDURE:

1. Fix one end of the helical spring to upperscrew.
2. Determine freelength.
3. Put some weight to platform and note down the deflection.
4. Stretch the spring through some distance and release.
5. Count the time required in Sec. for say 10, 20 oscillations.
6. Determine the actual period.
7. Repeat the procedure for different weights.

7.5 RESULTS:

Distances:

AB = m

BC = m

CD = m

DE = m

EA = m

Included Angles:

Angle A =

Angle B =

Angle C =

Angle D =

Angle E =

7.6 FURTHER PROBING EXPERIMENTS

1. When a body is subjected to transverse vibrations, the stress induced in a body will be?
2. The ratio of the maximum displacement of the forced vibration to the deflection due to the static force is known as.
3. The natural frequency (in Hz) of free longitudinal vibrations is equal to?
4. Define resonance. When a body is subjected to transverse vibrations, the stress induced in a body will be?
5. The ratio of the maximum displacement of the forced vibration to the deflection due to the static force is known as.
6. The natural frequency (in Hz) of free longitudinal vibrations is equal to?
7. Define resonance.

LAB-7 RADIATION METHOD, INTERSECTION METHODS BY PLANE TABLE SURVEY

8.1 OBJECTIVE:

To determine the frequency of different shafts.

8.2 RESOURCES:

1. Tape Linen Tape 20m
2. Ranging Rods 3m or 2m
3. Arrows
4. Plane Table with Tripod and its accessories
5. Two Drawing Sheets
6. Drawing Clips
7. Pencil, Eraser and Pins

8.3 PRECAUTIONS:

1. The plan must be so oriented on the sheet that the north side of the survey lies towards the top of the sheet
2. Leveling must be done carefully.
3. Readings must be taken with full accuracy
4. Ground points must be transferred to paper with full accuracy

8.4 THEORY:

SHAFT SUPPLIED WITH THE EQUIPMENT:

Polishing spring steel shafts are supplied with the machine, the dimensions being as under,

8.5 PROCEDURE:

At motor end as well as tail end different bearing blocks can be fixed which are as follows,

1. Supported end condition – Make use of end block with single self aligning bearing.

2. Fixed end conditionx – Make use of end block with doublebearing.
3. Guards D1, D2 and D3 –
4. The guards can be fixed at any position on the supporting frame which fits on the side supports. Rotating shafts are to be fitted in blocks in A and B stands.
5. SPEED CONTROL OF DRIVING MOTOR –
6. The driving motor is 240 volts, frictional HP, 5000 rpm, 50 Hz, and speed control unit is a Dimmerstat of 240 volts, 2 Amp. 50Hz.
7. MEASUREMENT OF SPEED –
8. To measure the speed of the rotating shaft a simple Tachometer may be used (will not be supplied with the equipment) on the opposite side of the shaft extension of the motor.
9. Whirling of elastic shaft –
10. If, L = Length of the shaft incm.
11. E = Young's Modulus Gpa = 73 in torsion and 193Gpa in tension I = 2nd moment of inertia of the shaft cm4.
12. W = Weight of the shaft per unit length Kg /cm. g = Acceleration due to gravity in m / sec2 = 9.81
13. Then the frequency of vibration for the various modes is given by the equation, $f = kx\sqrt{EIg}$

8.6 TYPICAL TEST OBSERVATION:

1. Both ends of shafts free (Support) 1st and 2nd mode of vibration can be observed on shafts with 3/16": dia. And 1/4" dia.
2. One end of shaft fixed and the other free, 1st and 2nd mode of vibration can be observed on the shaft with 3/16" dia.
3. Both ends of shaft fixed – 2nd mode of vibration cannot be observed on any of the shafts as the speeds are very high and hence beyond the range of the apparatus.
4. There is difference between theoretical speed of whirling and actual speed observed, due to following reasons:
 - (a) The end conditions are not as exact as assumed in theory.
 - (b) Pressure of damping at the end bearings.
 - (c) Assumptions made in theoretical predictions.
 - (d) Lack of knowledge of exact properties of shaft material.
 - (e) A uniformly loaded shaft has, theoretically infinite no. of natural frequencies of transverse vibration for fundamental mode observation of the first mode of whirling is therefore not so defined and thus difficult 2nd can be very easily observed.

8.7 RESULTS:

Given area is plotted on paper by Radiation and Intersection methods of Plane Table Survey.

8.8 FURTHER PROBING EXPERIMENTS

1. Define time period related to vibratory motion.
2. Define time cycle related to vibratory motion.
3. Name different types of free vibrations.
4. Define longitudinal vibrations.
5. Name different types of vibrations

LAB-8 TWO POINT PROBLEM IN PLANE TABLE SURVEY

9.1 OBJECTIVE:

To Study the Double Slider Crank and Geneva Mechanism

9.2 RESOURCES:

Double Slider Crank Mechanism
Geneva Mechanism

9.3 Theory:

DOUBLE SLIDER CRANK MECHANISM

Double Slider Crank Chain A four bar chain having two turning and two sliding pairs such that two pairs of the same kind are adjacent is known as double slider crank chain.

Inversions of Double slider Crank chain: It consists of two sliding pairs and two turning pairs. They are three important inversions of double slider crank chain. 1) Elliptical trammel. 2) Scotch yoke mechanism. 3) Oldham's Coupling.

1. Elliptical Trammel:

This is an instrument for drawing ellipses. Here the slotted link is fixed. The sliding block A and B in vertical and horizontal slots respectively. The end R generates an ellipse with the displacement of sliders A and B.

The co-ordinates of the point R are x and y. From the fig. $\cos\theta = \frac{x}{OR}$ and $\sin\theta = \frac{y}{OQ}$
Squaring and adding (i) and (ii) we get

The equation is that of an ellipse, hence the instrument traces an ellipse. Path traced

2. Scotch yoke mechanism: This mechanism, the slider A is fixed. When AB rotates above A, the slider B reciprocates in the vertical slot. The mechanism is used to convert rotary to reciprocating mechanism. Consider fig a and b.

GENEVA MECHANISM

INTRODUCTION

The Geneva drive or Maltese cross is a gear mechanism that translates a continuous rotation movement into intermittent rotary motion. The rotating drive wheel is usually equipped with a pin that reaches into a slot located in the other wheel (driven wheel) that advances it by one step at a time.

CLASSIFICATION OF GENEVA MECHANISM

1. External Gear Mechanism

In this type of mechanism, the Geneva cross is connected with cam drive externally which is the most popular and can withstand higher mechanical stresses. The driver grooves lock the driven

wheel pins during dwell. During movement, the driver pin with the driver-wheel slot.

2. Internal Gear Mechanism

In this type of mechanism the Geneva cross and cam drive are connected internally in the closed box. The driver and driven wheel rotate in same direction. The duration of dwell is more the 180° of driver rotation.

3. Spherical Geneva Mechanism

In this type of mechanism, the Geneva cross is in spherical shape and cam drive is connected in externally, which is extremely rare. The driver and driven wheel are on perpendicular shafts. The duration of dwell is exactly 180° of driven rotation.

Working of Geneva Mechanism

In the most common arrangement, the driven wheel has four slots and thus advances by one step of 90 degree for each rotation of the drive wheel. If the driven wheel has n slots, it advances by 360 degree per n full rotation of the drive wheel.

Geneva are also combined with variety of other mechanism, such as four bar linkages, clutch-brake combination, Non- circular gears etc to modify the motion curves and dwell motion ratios obtained from pure Geneva.

perpendicular shafts. The duration of dwell is exactly 180° of driven rotation.

Advantages of Geneva Mechanism

- a) Geneva Mechanism may be the simplest and least Expensive of all intermittent motion mechanism.
- b) They come in a wide variety of sizes, ranging from those used in instrument, to those used in machine tools to index spindle carriers weighing several tons.
- c) They have good motion curves characteristics compared to ratchets, but exhibit more “jerk” or instantaneous change in acceleration, than better cam systems.

Disadvantages of Geneva Mechanism

- a) The Geneva is not a versatile mechanism and produce jerk.
- b) The ratio of dwell period to motion is also established once the no of dwells per revolution has been selected.
- c) All Geneva acceleration curves start and end with finite acceleration and deceleration.

Application of Geneva Mechanism

- It is applicable in the production industries and automobile industries for mass production.
- Modern film projectors may also use an electronically controlled indexing mechanism or stepper motor, which allows for fast-forwarding the film.
- Geneva wheels having the form of the driven wheel were also used in mechanism watches, but not in a drive, rather to limit the tension of the spring, such that it would operate only in the range where its elastic force is nearly linear.
- Indexing table in assembly lines, tool changers for CNC machine, and so on.

9.4 PROCEDURE:

In this method two stations are so selected that all the other stations to be plotted are visible from these. The line joining these two stations is called Base Line. The length of this line is measured very accurately. Rays are drawn from these stations to the stations to be plotted. The intersection of the rays from the two stations gives the position of the station to be plotted on the drawing sheet. Let A and B be the two accessible stations (Fig 3), such that A and B can be suitably plotted. C is the station to be plotted by intersection. The plane table is placed at A. N – S direction is plotted. The ground station A is transferred as „a onto the drawing

sheet. With the alidade centered at , station B is sighted. A ray aB is drawn and is cut as ab to a suitable scale. With the alidade at , C is also sighted and a ray aC is drawn. The table is now shifted to B and is setup. The alidade is placed at b and C is sighted. A ray bC is drawn. The intersection of the two rays gives the position of C as on the plane table

9.5 RESULTS:

The required instrument station C is occupied by using two point problems

9.6 FURTHER PROBING EXPERIMENTS

1. Define machine & structure.
2. Concept of kinematics links, pairs, chains & mechanism.
3. Classification & examples of all the kinematics links, pairs, chains & mechanism.
4. Grashof's criterion.
5. Types & examples of constrained motion.

LAB-9 THREE POINT PROBLEM IN PLANE TABLE SURVEY

10.1 OBJECTIVE:

To find the required stations by using three point problem.

10.2 RESOURCES:

Write the text here

10.3 THEORY:

FUNCTION OF TRANSMISSION BOX (GEAR BOX) IN AUTOMOBILE:

The transmission box which is also known as the gear box is the second element of the power train in an automobile. It is used to change the speed and torque of vehicle according to variety of road and load conditions. Transmission box change the engine speed into torque when climbing hills and when the vehicle required. Sometimes it is known as torque converter. Main functions of a gear box are as follow:

1. Provide the torque needed to move the vehicle under a variety of road and load conditions. It does this by changing the gear ratio between the engine crankshaft and vehicle drive wheels.
2. Be shifted into reverse so the vehicle can move backward.
3. Be shifted into neutral for starting the engine.

MAIN COMPONENTS OF A GEAR BOX:

In any device two or more component works together and full fills the required function. In a transmission box four components are required to fulfil its function. These components are-

a) Counter shaft:

Counter shaft is a shaft which connects with the clutch shaft directly. It contains the gear which connects it to the clutch shaft as well as the main shaft. It may be run at the engine speed or at lower than engine speed according to gear ratio.

b) Main shaft:

It is the shaft which runs at the vehicle speed. It carries power from the counter shaft by use of gears and according to the gear ratio, it runs at different speed and torque compares to counter shaft. One end of this shaft is connects with the universal shaft.

c) Gears:

Gears are used to transmit the power from one shaft to another. They are most useful component of gear box because the variation is torque of counter shaft and main shaft is depends on the gear ratio. The gear ratio is the ratio of the driven gear teeth to the driving gear teeth. If gear ratio is large than one, the main shaft revolves at lower speed than the counter shaft and

the torque of the main shaft is higher than the counter shaft. On other hand if the gear ratio is less than one, than the main shaft revolves at higher speed than the counter shaft and the torque of the main shaft is lower than the counter shaft. A small car gear box contains four speed gear ratio and one reverse gear.

d) Bearings:

Whenever the rotary motion encounters, bearings are required to support the revolving part and reduce the friction. In the gear box both counter and main shaft are supported by the bearing.

WORKING OF A PRINCIPLE GEAR BOX:

In a gear box, the counter shaft is meshed to the clutch with a use of a couple of gears. So the counter shaft is always in running condition. When the counter shaft is bring in contact with the main shaft by use of meshing gears, the main shaft start to rotate according to the gear ratio. When driver want to change the gear ratio, simply press the clutch pedal which disconnect the counter shaft with engine and connect the main shaft with counter shaft by another gear ratio by use of gearshift lever. In an gear box, the gear teeth and other moving metal must not touch. They must be continuously separated by a thin film of lubricant. This prevents excessive wear and early failure. There for a gearbox runs partially filled with lubricant oil.

SELECTIVE TYPE GEAR BOX

It is the transmission in which any speed may be selected from the neutral position. In this type of transmission neutral position has to be obtained before selecting any forward or reverse gear. Some selective type gear boxes are,

1. Sliding mesh gear box
2. Constant mesh gear box with positive dog clutch.
3. Constant mesh gear box with synchromesh device.

1. SLIDING MESH GEAR BOX

- a) It is the simplest and oldest type of gear box.
- b) The clutch gear is rigidly fixed to the clutch shaft.
- c) The clutch gear always remains connected to the drive gear of countershaft.
- d) The other lay shaft gears are also rigidly fixed with it.
- e) Two gears are mounted on the main shaft and can be sliding by shifter yoke when shifter is operated.
- f) One gear is second & top speed gear and the other is the first and reverse speed gears. All gears used are spur gears.
- g) A reverse idler gear is mounted on another shaft and always remains connected to reverse gear of counter shaft.

First Gear

- a) By operating gearshift lever, the larger gear on main shaft is made to slide and mesh with first gear of countershaft.
- b) The main shaft turns in the same direction as clutch shaft in the ratio of 3:1.

Second Gear

- a) By operating gear shift lever, the smaller gear on the main shaft is made to slide and mesh with second gear of counter shaft.
- b) A gear reduction of approximately 2:1 is obtained.

Top Gear

- a) By operating gearshift lever, the combined second speed gear and top speed gear is forced

axially against clutch shaft gear.

b) External teeth on clutch gear mesh with internal teeth on top gear and the gear ratio is 1:1.

Reverse Gear

a) By operating gearshift lever, the larger gear of main shaft is meshed with reverse idler gear.

b) The reverse idler gear is always on the mesh with counter shaft reverse gear. Interposing the idler gear, between reverse and main shaft gear, the main shaft turns in a direction opposite to clutch shaft.

Neutral Gear

a) When engine is running and the clutch is engaged, clutch shaft gear drives the drive gear of the lay shaft and thus lay shaft also rotates.

b) But the main shaft remains stationary as no gears in main Shaft is engaged with lay shaft gears.

CONSTANT MESH GEAR BOX

a) In this type of gearbox, all the gears of the main shaft are in constant mesh with corresponding gears of the countershaft.

b) The gears on the main shaft which are bushed are free to rotate.

c) The dog clutches are provided on main shaft.

d) The gears on the lay shaft are, however, fixed.

e) When the left Dog clutch is slide to the left by means of the selector mechanism, its teeth are engaged with those on the clutch gear and we get the direct gear.

f) The same dog clutch, however, when slide to right makes contact with the second gear and second gear is obtained.

g) Similarly movement of the right dog clutch to the left results in low gear and towards right in reverse gear. Usually the helical gears are used in constant mesh gearbox for smooth and noiseless operation.

Advantage over sliding mesh gear box

- Helical and herringbone gear can be used in these gear boxes and therefore, constant mesh gearboxes are quieter.

- Since the gears are engaged by dog clutches, if any damage occurs while engaging the gears, the dog unit members get damaged and not the gear wheels.

Double declutching

- Used for smooth downshifting.

2. SYNCHROMESH GEARBOX

This type of gearbox is similar to the constant mesh type gear box.

a) Instead of using dog clutches here synchronizers are used.

b) The modern cars use helical gears and synchromesh devices in gearboxes, that synchronize the rotation of gears that are about to be meshed

SYNCHRONIZERS

a) This type of gearbox is similar to the constant mesh type in that all the gears on the main shaft are in constant mesh with the corresponding gears on the lay shaft.

b) The gears on the lay shaft are fixed to it while those on the main shaft are free to rotate on the same.

c) Its working is also similar to the constant mesh type, but in the former there is one definite improvement over the latter.

d) This is the provision of synchromesh device which avoids the necessity of double- declutching.

- e) The parts that ultimately are to be engaged are first brought into frictional contact, which equalizes their speed, after which these may be engaged smoothly.
- f) Figure shows the construction and working of a synchromesh gearbox. In most of the cars, however, the synchromesh devices are not fitted to all the gears as is shown in this figure.
- g) They are fitted only on the high gears and on the low and reverse gears ordinary dog clutches are only provided.
- h) This is done to reduce the cost.

Note:-

The Model Gear Box Is Synchromesh Gear Box with 3 Forward and Single Reverse Gear.
Some Other Transmission Used In Modern Automobile

TRANSFER CASE

- Normally used in 4 wheel drive vehicles.
- Two speed transmission having "low and high" rear ratios that can be engaged while in neutral position.
- Fixed after the gear box.
- Enables engagement and disengagement of 4 wheel drive.

TRANSAXLE GEAR BOX

- Have only 2 shafts.
- Used in vehicle with engine and drive on some side.
 - Front engine front wheel drive.
 - Rear engine rear wheel drive.
- Most commonly used.
- Gear box and differential in same housing.
- Combination of transmission and differential in one unit is called transaxle.
- Transaxles are both automatic and manual.

10.4 PROCEDURE:

1. Plot a, b,c as in the ground.
2. The length of ab, bc and ac are given. It forms a triangle.
3. The alidade place along CA.
4. The board rotates till the point A is sighted and the board is clamped.
5. Pivot the alidade on a and sight to b and draw a ray .These two ray will meet at a point
6. Then joint bd, and rotate the board till the point B is sighted and draw a back ray.
7. This ray will meet at a point on the line bd, this will be the required station.

10.5 RESULT

The required instrument station C is occupied by using three point problem

LAB-10 TRAVERSING BY PLANE TABLE SURVEY

11.1 OBJECTIVE:

- To study the forced vibration of the beam for different damping.

11.2 RESOURCES:

- Vibration test rig
- Cantilever Beam
- Rubber hammer

11.3 PRECAUTIONS:

1. Do not run the motor at low voltage i.e. less than 180 volts.
2. Do not increase the speed at once.
3. Damper is always in perpendicular direction.
4. A motor bolts is properly tightly with weight.
5. A beam is proper tight in bearing with bolt.
6. Always keep the apparatus free from dust.

11.4 PROCEDURE:

1. Arrange the setup
2. Connect the exciter motor to control panel.
3. Start the motor and allow the system to vibrate.
4. Wait for 5 minutes for amplitude to build up for particular forcing frequency.
5. Adjust the position of strip chart recorder. Take the recorder of amplitude vs. Time on strip chart recorder by starting recorder motor.
6. Take record by changing forcing frequency for each damping.
7. Repeat the experiment for different damping.

11.5 GRAPH:

- Plot the graph of amplitude Vs. Frequency for each damping

11.6 RESULTS:

Traversing method for running survey lines of a closed or open traverse is done.

11.7 FURTHER PROBING EXPERIMENTS

1. Define free vibrations.
2. Define forced vibrations.
3. Define torsional vibrations.
4. Define longitudinal vibrations.
5. Define frequency related to vibratory motion.